




HARRIS AERIAL



Carrier H6 Electric

GENERAL


Maximum Takeoff Weight	55 lbs 25 kg
Empty Weight	21.5 lbs 9.8 kg
Max Payload	17.6 lbs 8 kg
Flight Time	48 min. (No Payload)
Max Speed	33.6 mph 15 m/s
Max Vertical Speed	5.6 mph 2.5 m/s
Max Lean Angle	30 degrees
Dimensions (Unfolded)	- Prop Tip to Tip: 2363.4 mm -Landing Gear Base: Length: 614.7 mm Width 654.1 mm



Flight modes	- GPS LOITER - ALTITUDE HOLD -FULLY AUTONOMOUS
Radio Frequencies	2.4 GHz (ISM) 902-928 MHz
System Architecture	Open Source
GPS	Dual RTK GNSS
Payload Mounting	Dampened Modular Quik-Release
Weather Rating	Light Rain
Flight Safety Systems	- Radio Connectivity Monitoring - Battery Voltage & Amperage Monitoring
Dimensions (folded)	- Height (Customizable): 620 mm - Length: 725 mm - Width: 780 mm

POWERPLANT AND BATTERIES

Battery Type	1251P Smart Lipo (2x Batteries)
Peak Battery Voltage	50.4 V
Nominal Battery Voltage	44.4 V
Auxiliary Power	5.3 V, 12 V, 24 V, 48 V Power Ports



Battery Capacity	16,000 mAh
Battery Life Cycle	250 Flights
Battery Connector	AS150U-F (Anti-Spark)
Safety Features	Battery Voltage & Amperage Monitoring

info@harrisaerial.com

www.harrisaerial.com

(407) 725-7886



Carrier H6 Electric

OPERATION AND ENVIRONMENTAL



Operation Temp	-20°C to 49°C -4°F to 120°F
Max Operational Wind Speed	25 mph 11 m/s

Service Ceiling AMSL	12,000 ft 3658 m (Payload Dependant)
Service Ceiling AGL	400 ft 122 m (FAA Limited)

MOTORS AND PROPELLERS



# Motors	6
Equivalent KV	KV100 Motors
Optimal RPM	2200 - 2800 RPM

Motor Configuration	HEXA X
Propeller Material	Carbon Fiber with Aluminum Hub
Propeller Dimensions	29.2 in x 9.2 in


COMMAND AND CONTROL



Harris C-GCS	<ul style="list-style-type: none"> - 19 in Dual HD Display - Hands-on Throttle-and-Stick (HOTAS) - Freq; 902 - 928 MHz - 12 Channel Functionality - NDAA Compliant
---------------------	---

hereLink	<ul style="list-style-type: none"> - Handheld Remote - 5.5 in Display - Freq: 2.4 GHz (ISM) - 32 Channels Functionality - NDAA Compliant
-----------------	---

FLIGHT CONTROLLER



Flight Controller	Cube Orange
Data Transmission Range	12.5 mi 20 km (Ideal Conditions)
Firmware	Custom ArduPilot

Takeoff and Landing	Autonomous or Manual Control
Flight Tracking	ADS-B (Receiver)
Safety Features	<ul style="list-style-type: none"> - Triple Redundant IMU - Redundant Power Supply